# **Specifications**

#### Material

» Co-extruded impact acrylic

#### Finish

» Textured

### Minimum Sheet Size

» 24" x 48¾" (610 x 1238mm)

#### Thickness 2-ply

- » 1/16" (1.6mm)
- » 1/8" (3.2mm) A Use 842 as first digits in item code. (Gauges are approximate.)

## **Cutting Depth**

- » .007" (.18mm)
- » Acid Yellow and Pimento is .010" (.25mm)

#### **Engraving Method**

- » Laser
- » Rotating carbide

#### Usage

- » Interior signage
- » Exterior signage
- » Safety signage
- » Industrial applications
- » Personal identification

# **Fabrication**

» Saws When sawing Textures, keep finished side down. » Hot stamps

» Bevels

» Bonds

» UV stable

» Drills

- » Laser vector cuts » Heat bendable
- » Screen prints
- » Permits fine detail engraving
- » Outdoor weatherable

Visit www.rowmark.com for Rowmark's complete line of products for rotary engraving, laser engraving and sublimation.

Find answers to all your auestions in the Technical Help section. Be sure to check out support tools under the Sales Tools and Downloads sections.

To request a sample or promotional literature, please call 1-877-ROWMARK (419-429-3160) or email samples@rowmark.com. For technical assistance, call 1-877-ROWMARK (419-429-3160), visit www.rowmark.com or email inquiries@rowmark.com.

Can't find exactly what you're looking for? Contact your authorized Rowmark distributor or speak with one of our customer service specialists at 1-800-243-3339 (419-425-2407).

5/11 



Textures<sup>™</sup> Sign Kit

item #9033

You may place your Textures<sup>™</sup> Sign Kit order at www.rowmark.com, or fabricate the signs on your own using the file found under the downloads section of our website.

# lexiures













rowmark.com / 1.877 ROWMARK / samples@rowmark.com



